



Europäisches  
Patentamt

European  
Patent Office

Office européen  
des brevets

REC'D 23 NOV 2004

WIPO

PCT

BEST AVAILABLE COPY

Bescheinigung

Certificate

Attestation

Die angehefteten Unterla-  
gen stimmen mit der  
ursprünglich eingereichten  
Fassung der auf dem näch-  
sten Blatt bezeichneten  
europäischen Patentanmel-  
dung überein.

The attached documents  
are exact copies of the  
European patent application  
described on the following  
page, as originally filed.

Les documents fixés à  
cette attestation sont  
conformes à la version  
initialement déposée de  
la demande de brevet  
européen spécifiée à la  
page suivante.

Patentanmeldung Nr. Patent application No. Demande de brevet n°

03024855.3

Der Präsident des Europäischen Patentamts;  
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets  
p.o.

R C van Dijk

**PRIORITY  
DOCUMENT**

SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH RULE 17.1(a) OR (b)



Anmeldung Nr:  
Application no.: 03024855.3  
Demande no:

Anmeldetag:  
Date of filing: 31.10.03  
Date de dépôt:

Anmelder/Applicant(s)/Demandeur(s):

Nestlé Waters Management & Technology  
20, rue Rouget de Lisle  
92130 Issy-les-Moulineaux  
FRANCE

Bezeichnung der Erfindung/Title of the invention/Titre de l'invention:  
(Falls die Bezeichnung der Erfindung nicht angegeben ist, siehe Beschreibung.  
If no title is shown please refer to the description.  
Si aucun titre n'est indiqué se référer à la description.)

A container for product with less packaging material

In Anspruch genommene Priorität(en) / Priority(ies) claimed / Priorité(s)  
revendiquée(s)  
Staat/Tag/Aktenzeichen/State/Date/File no./Pays/Date/Numéro de dépôt:

Internationale Patentklassifikation/International Patent Classification/  
Classification internationale des brevets:

B65D/

Am Anmeldetag benannte Vertragstaaten/Contracting states designated at date of  
filing/Etats contractants désignées lors du dépôt:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LU MC NL  
PT RO SE SI SK TR LI

- 1 -

**A container for product with less packaging material.**

The present invention relates to the field of the packaging of flowable products such as liquids or pasty products , particularly that of containers intended to  
5 contain beverages and more especially mineral water.

One topic in the packaging area, especially for water is to reduce the weight of the plastic material used, and  
10 more particularly to reduce the weight of the bottom of the container. By reducing the weight of the bottom, the first danger is that said bottom is less resistant because of the fact that the bottom is really the part of the container , which is the more submitted to  
15 constraints, due to the contact of said bottom with the place where it is disposed. There are already some solutions to that problem, like the container with petaloid bottom : the FR Patent No. 2772720 concerns such a container, wherein the bottom is thinner. Although this  
20 patent brings a solution for the bottom, it remains a container with a too high amount of plastic material for the volume of the product filled in said container.

The objective of the present invention is to have a  
25 container for a flowable product with a bottom allowing said container to stand and which for the same volume requires less plastic than a standard container while at the same time having comparable or higher mechanical properties.

30 The subject of the present invention is a container comprising a body formed by walls and a bottom having in his greater section a dimension  $d_1$  and a neck with an internal diameter  $d_2$  , said container being made from a  
35 semi-crystalline PET , the body of said container comprising at its bottom at least three feet spaced from each other and being integral with said body, wherein for the body, the ratio weight of the walls on weight of the

- 2 -

bottom is comprised between 3 and 4 and wherein the ratio volume of the body of the container per gram of PET of the body is comprised between 80 and 120. The volume is given in ml.

5

Under bottom in the present description, we understand all the part of the body comprising the space of said body outside the feet, said feet being taken from their most external position.

10

Semi-crystalline PET means in the present specification a PET having a crystallinity comprised between 10 and 60 %. More preferably, the crystallinity is comprised between 20 and 40 %.

15

One specificity of the invention is that the container has feet at the bottom, which are integral with said body. The presence of three feet is a good solution, but for greater volume a presence of 4 or 5 feet is preferred. The geometry of said feet is not critical. Preferably, these feet have a spherical geometry. Concerning the bottom of the container, it has preferably a non flat form. The bottom has a convex form, like a semi-spherical form.

25

It is possible for the container of the invention, either to have a neck with a small height, like a couple of millimeters, or to have a neck with a greater height. In this case, the ratio height of the neck on the height of the body is comprised between 1:1 and 1:4. This allows for the consumer a better gripping of said container.

30

THE INVENTION IS NOT LIMITED BY THE ABOVE-DESCRIBED EMBODIMENTS AND VARIATIONS THEREOF. THE SCOPE OF THE INVENTION IS DEFINED BY THE CLAIMS.

- 3 -

In the container of the invention, the part of the bottom between the feet has a greater thickness of that of the walls, for example around 100-200  $\mu\text{m}$ .

- 5 The present invention concerns further a packaging assembly comprising
- a container comprising a body formed by walls having in his greater section a dimension  $d_1$  and a neck with an internal diameter  $d_2$ , said container being made from a
- 10 semi-crystalline PET, the body of said container comprising at its bottom at least three feet spaced from each other and being integral with said body, wherein for the body, the ratio weight of the walls on weight of the bottom is comprised between 3 and 4 and wherein the ratio
- 15 volume of the body of the container per gram of PET of the body is comprised between 80 and 120,
- a product in the container and
  - closing means for closing off or distributing the product from the neck,
- 20 the filled container being substantially incompressible by hand when filled with the product.

This incompressibility applies for all types of products, even for a still product. In the present specification,

25 incompressible means that when squeezed the filled container only deforms very slightly and then will recover its original shape. In contrast, a standard bottle will buckle and deform.

30 According to a feature of the invention, the container comprises on its outside a printing made by pad printing. The advantage of this solution, is that it suppresses the need of having a paper stuck around the container.

35 The volume of the container used according to the invention can have all type of capacity, comprised between 5 cl and 20 l capacity. The container is intended to contain all type of product, like pasty, liquid, semi-

- 4 -

liquid, granular or powdered product. Under liquid product, we understand water or a still liquid beverage, particularly still mineral waters, carbonated water or a carbonated liquid beverage, particularly sparkling mineral water. Other types of liquid products are also possible, like chemical products, oil, essence, perfumes, pharmaceutical products. Under pasty products, we understand food and non food products, like mayonnaise, cosmetic compounds and others.

The means of closing are either a cap, or sealed membrane. The caps can be used for any diameter of opening of the neck. On the contrary, the sealed membranes are preferred with smaller diameter of the neck, for example in the area of 10 mm. In this case, the container can support high compressions, for example by the storage and by the transportation. For diameters of around 10 mm, the container can support an internal pressure of the order of 5 bar. It is also possible to close the container by sealing or welding the neck, wherein a cutting object or similar is provided for the opening.

As a preference, the container has an ovoid or substantially ovoid overall shape. This natural shape derived from an egg represents a structure whose resistance to vertical and/or transversal loads is optimized, thus making it possible, for a given volume and a given amount of material, to achieve mechanical properties which are equivalent to or even better than the cylindrical or roughly cylindrical shapes customarily encountered in this domain.

- 5 -

This is because the geometry with symmetry of revolution is particularly easy and therefore economical to manufacture and has the advantage of allowing the container to be filled with products which can emit  
5 gaseous substances, such as carbonated beverages (sparkling waters, sodas, etc.) in particular, which are widely consumed worldwide these days. Such a shape is therefore particularly well suited to these liquids in that the release of carbon dioxide or other gas has a  
10 tendency to deform the bodies of bottles which do not have symmetry of revolution, having a negative impact on their stability, grasp and ease of handling, appearance, etc.

15 In a preferred feature of the invention, the ratio  $d_2$  on  $d_1$  of the container is comprised between 1:3 and 1:10. According to a preferred embodiment of the packaging assembly, the ratio weight of the walls on weight of the bottom is comprised between 3.4 and 3.8. According to a  
20 further preferred feature of the invention, the ratio volume of the body of the container per gram of PET of the body is comprised between 90 and 110.

According to another feature, the plastic used to form  
25 the wall or walls is a semicrystalline plastic with a slow rate of crystallization, the glass transition temperature ( $T_g$ ) of which is 70°C or higher and the cristallisation temperature  $T_c$  is around 140 °C. A slow rate of crystallization is to be understood as  
30 meaning a rate which makes it possible to have an amorphous state by quick cooling.

Advantageously, the plastic used to form the wall or  
walls is chosen from the group formed by PET  
35 (polyethylene terephthalate) and PEN (polyethylene naphthalate). It has been noted that the drawing of the PET has no negative influence on the water barrier properties of the obtained container and that also a

- 6 -

thickness of around 50  $\mu\text{m}$  and less guarantees a good safety of the container itself and of the storage.

In order to guarantee both the flexibility needed for the aforementioned deformation and sufficient mechanical

5 strength, the container according to the invention is further characterized in that the thickness of the wall or walls forming the body of the container is between 30  $\mu\text{m}$  and 100  $\mu\text{m}$ , preferably between 50  $\mu\text{m}$  and 70  $\mu\text{m}$ .

10 As already mentioned, small thicker areas or portions of walls may also be provided on the body of the said container, particularly in close proximity to the neck and/or the bottom, so as to reinforce these parts locally. Such reinforcements may in particular be useful to facilitate the filling of the said containers or to

15 increase their stability during storage.

As a preference, the container is further characterized in that the body and the neck of the container are made as a single piece. This makes it possible to avoid any join or weld which may constitute a region of greater

20 weakness.

Indeed, according to another feature, the container according to the invention is characterized in that, it has a high resistance to vertical and/or transverse loads

25 allowing good resistance to transportation. For example, for a working volume of 5 litres, the amount of PET used to produce the said container is about 30 g. for resistance to a vertical load of about 65 kg. This represents a significant saving in plastic, the few 5-

30 litre containers that are currently on the market requiring an amount of polymer which, for comparable mechanical strength, is over two times greater than the



- 7 -

container supports a vertical loading of more than about 100 kg. That the container supports a vertical or transverse loading means that the weight given does not deteriorate the package integrity, that is does not lead  
5 to a risk of breaking said container.

These simple shapes also allow the container according to the invention to be used as a refill or recharge for water coolers, for which a flat bottom is not necessary,  
10 these refills generally being used by inserting the container, head (neck) downmost, into the accommodation device of the said water cooler. In addition, this type of surface geometry also makes it possible to increase the area of heat exchange between the said container and  
15 the chilling device usually present in the said water coolers.

According to another alternative form, the container according to the invention is characterized in that the  
20 neck is fitted with a closure and/or distribution means produced in the form of a distribution tap which can be operated with one hand.

Such distribution taps, which are known per se,  
25 advantageously allow the distribution of the flowable product contained in the container to be regulated in a particularly convenient way, for example when this container is stored horizontally on the shelves of a refrigerator, the other hand holding the container into  
30 which the said flowable product is to be transferred, for example with a view to consuming it.

Because of its flexible nature, the geometry of the container can also adapt more readily to that of the storage place, as opposed to the rigid cans currently  
35 available which need to observe very specified dimensions in order to be able to be stored in restricted spaces such as the internal compartments of refrigerators. In addition, the space freed as a container according to the

- 8 -

invention is emptied can also be put to use for storing objects the size or shape of which can vary, which is not the case with rigid containers in which the volume of liquid removed is systematically replaced with air. In  
5 this type of container, the volume initially occupied remains so until the empty container is removed from the refrigerator.

Another subject of the present invention is the use of  
10 the container by way of large-capacity, at least 5-litre capacity, container intended to contain water or a still liquid beverage, particularly still mineral water.

Another subject of the present invention is the use of the container according to the invention by way of large-  
15 capacity, at least 5-litre capacity, container intended to contain carbonated water or a carbonated liquid beverage, particularly sparkling mineral water.

Of course, the containers of the present invention are not in any way limited to flat or sparkling mineral  
20 waters but can be intended to contain all sorts of flowable products, edible or inedible liquids of greater or lesser fluidity such as, for example, fruit juices, milk-based beverages, etc., and also sauces or condiments (ketchup, mustard, dressing, etc.) or non-food liquids  
25 (deionized water, cleaning products, detergents, etc.).

The packaging assembly according to the invention can also contain a functional component. The functional component is taken from the group consisting of a fibre,  
30 plant extract, fruit extracts, vitamins and flavors. The assembly is pasteurized or sterilized at a temperature in excess of 60 °C.

- 9 -

stretching of a preform. The blow forming can be also a blow molding. Compared with the blowing of plastic bottles, wherein the blowing pressure is comprised between 30 and 40 bar, according to the process of the invention, it is sufficient to blow at a pressure of  
 5 around 2 times less. This reduces the cost of the process and also of the machine which is used. Concerning the stretch index, it is depending of the volume of the final container. For example, in the case of a container  
 10 having a volume of less than 100cl, the stretch index is between 100 and 300 cm. In the case of a container having a volume of 500 to 1000 cl, the stretch index is comprised between 500 and 700 cm. In the case of  
 15 container having volume of 2000 cl or more, the stretch index is around and more than 1000 cm.

The stretch index is defined as follows :

20 Stretch index =  $\frac{\text{internal volume of the stretched container}^*}{\text{internal volume of the preform before stretching}^*} \times 1$

$f = \frac{\text{internal surface of the container}^*}{\text{internal volume of the stretched container}^*} \quad (\text{cm}^{-1})$

25 \* with the exclusion of the neck

In the embodiments of the containers according to the invention, for volumes of 33 cl, 1 liter, 5 l, 10 l and 20 l, the different ratios S2 on S1 are comprised between  
 30 1:4.5 and 1:15.

Because of the substantial incompressibility of the filled container of the invention, there is no need to have reinforcing structures. The consequence is that it  
 35 is possible to have simple shapes, which have the advantage of providing transparency and purity. This is particularly important for the consumer in the case of a container for drinking water. Another advantage of this

- 10 -

container is that it can be emptied without air coming in and this reduces the risk of contamination or odours entering the product that may cause taste changes or degradation.

5

The measure of the crystallinity is made on a density column from Lloyd-Davenport, according to following procedure. The column is filled with a salted solution (calcium nitrate) having a density gradient. The column is calibrated with balls having known density between 1.335 and 1.455. Then small pieces of the container of the invention are immersed in the column and after a certain time, they stay at a certain height of the column corresponding to a certain density. The measures are made at 23 °C. The following correspondance table with  $\rho_c$  of 1.455 gives the cristallinity

Density ( $\rho_c$ )	Crystallinity (%)
1.335	0%
1.345	5.6
1.355	11.1
1.365	16.7
1.375	22.2
1.385	27.8
1.395	33.3
1.405	38.9
1.415	44.4
1.425	50.0
1.435	55.6
1.445	61.1
1.455	66.7
1.465	72.2
1.475	77.8
1.485	83.3
1.495	88.9
1.505	94.4
1.515	100.0

- 11 -

Other features and advantages of the invention will become apparent from the description which follows, given by way of example and with reference to the appended drawings in which:

5

Fig. 1 is a lateral perspective view of the container according to the invention,

10

Fig. 2 is another perspective view of the container of the invention, seen from the bottom and

Fig. 3 is a graph comparing the invention with the state of the art.

15

In the embodiment described and depicted on figures 1 and 2, the container for a flowable product, particularly for a beverage and, in particular, for mineral water, essentially consists of a body 1, formed by walls 2 and a bottom 3 and a neck 4. The body is made of a semi-

20

crystalline PET. The neck presents a screw 5 for receiving a cap (not shown). The bottom 3 presents three feet 6 integral with the body. The volume of the container is of 1000 ml. In this specific example the

25

ratio weight of the walls on weight of the bottom is of 3.5 and the ratio volume of the body of the container per gram of PET is of 100. This means that for the volume of 1000 ml, there is 10 g of PET for the body (neck

30

excluded). The thickness of the walls is around 70  $\mu\text{m}$ . The neck has a height which is minimised and said neck has a wall thickness of around 200  $\mu\text{m}$ . In the area 7 of the feet, that means around the middle of said feet, the wall thickness is around 150  $\mu\text{m}$ . The feet have a semi-

35

spherical shape. Concerning now the limits of the wall and bottom for calculating the ratio weight of the walls on weight of the bottom, it is outside and inside of the circle 8 of figure 2.

- 12 -

Concerning now the graph of figure 3, the x axis represents the volume of the container in ml and the y axis represents the ratio volume of the container in ml per g of the plastic material of said container. The graph 1 shows a bottle used on the market for sparkling water. The graph 2 shows a bottle used on the market for still water and the graph 3 shows a container according to the invention. This graph shows very clearly one of the specificity of the invention, which is that less plastic material is needed for conditioning the same volume of product, Taking an example of the graph : according to the invention 1 g of plastic material is needed for 100 ml of product, whereas for products now on the market 1 g of plastic material is needed for only around 40 to 60 ml of product. That means that according to the invention, the need of plastic material is divided by 2.

- 13 -

**Claims.**

- 1) A container comprising a body formed by walls and a bottom having in his greater section a dimension  $d_1$  and a neck with an internal diameter  $d_2$  , said container being made from a semi-crystalline PET , the body of said container comprising at its bottom at least three feet spaced from each other and being integral with said body, wherein for the body, the ratio weight of the walls on weight of the bottom is comprised between 3 and 4 and wherein the ratio volume of the body of the container per gram of PET of the body is comprised between 80 and 120.
- 2) A container according to claim 1, wherein the walls of the body have a thickness of less than 100  $\mu\text{m}$ .
- 3) A container according to any of claims 1 or 2, wherein the neck has a wall thickness comprised between 150 and 250  $\mu\text{m}$ .
- 4) A container according to any of claims 1 to 3, wherein each foot has a wall thickness comprised between 50 and 150  $\mu\text{m}$ .
- 5) A container according to any of claims 1 to 4, wherein the part of the bottom between the feet has a greater thickness of that of the walls.
- 6) A packaging assembly comprising  
- a container comprising a body formed by walls having in his greater section a dimension  $d_1$  and a neck with an internal diameter  $d_2$  , said container being made from a semi-crystalline PET , the body of said container comprising at its bottom at least three feet spaced from each other and being integral with said body, wherein for the body, the ratio weight of the walls on weight of the bottom is comprised between 3 and 4 and wherein the ratio

- 14 -

volume of the body of the container per gram of PET of the body is comprised between 80 and 120,

- a product in the container and

- closing means for closing off or distributing the

5 product from the neck,

the filled container being substantially incompressible by hand when filled with the product.

7) A packaging assembly according to claim 6, wherein the  
10 product is taken from the group consisting of pasty, liquid, semi-liquid, granular or powdered product.

8) A packaging assembly according to any of claims 6 or  
15 7, wherein said assembly has a high resistance to vertical and/or transverse loads allowing good resistance to transportation.

9) A packaging assembly according to claim 8, wherein  
20 said assembly supports a vertical and/or transverse loading of more than about 100 kg for a container having a weight of about 4 g.

10) A packaging assembly according to any of claims 4 to  
25 9, wherein the body of the container has a form taken from the group consisting of a three dimensional shape convenient for gripping, an ovoid, spherical, elliptical or cylindrical shape.

11) A packaging assembly according to any of claims 4 to  
30 10, wherein the wall thickness of the body, substantially in the middle of its body is comprised between 30 and 70

mm



- 15 -

- 13) A packaging assembly according to any of claims 4 to 12, wherein the ratio  $d_2$  on  $d_1$  is comprised between 1:3 and 1:10.
- 5 14) A packaging assembly according to any of claims 4 to 13, wherein the ratio height of the neck on the height of the body is comprised between 1:1 and 1:4.
- 10 15) A packaging assembly according to any of claims 4 to 14, the ratio weight of the walls on weight of the bottom is comprised between 3.4 and 3.8.
- 15 16) A packaging assembly according to any of claims 4 to 15, wherein the ratio volume of the body of the container per gram of PET of the body is comprised between 90 and 110.
- 20 17) A process for manufacturing the container according to any of claims 1 to 5, wherein said container is obtained by stretch blow forming of a PET preform with high stretch index in comparison with the classical stretching of a preform.


- 16 -

**Abstract**

**A container for product with less packaging material.**

5 The invention concerns a container comprising a body 1  
formed by walls 2 and a bottom 3 having in his greater  
section a dimension  $d_1$  and a neck 4 with an internal  
diameter  $d_2$ , said container being made from a semi-  
crystalline PET, the body of said container comprising  
10 at its bottom at least three feet spaced from each other  
and being integral with said body, wherein for the body,  
the ratio weight of the walls on weight of the bottom is  
comprised between 3 and 4 and wherein the ratio volume of  
the body of the container per gram of PET of the body is  
15 comprised between 80 and 120.

**Figure 1.**






FIG.2




FIG. 3.

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record.**

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☒ **FADED TEXT OR DRAWING**
- ☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☒ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

## **IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**